

J+J Stellantrieb Multi-Voltage 85 - 240 AC/DC

Spezifikation	Modell J2-H10	Modell H20	Modell H35	Modell H55	Model H140
Spannung	85 - 240 VAC/VDC -0/+5% 50/60 Hz	85 - 240 VAC/VDC 50/60 Hz	85 - 240 VAC/VDC 50/60 Hz	85 - 240 VAC/VDC 50/60 Hz	85 - 240 VAC/VDC 50/60 Hz
Stellzeit (s/90°) ±10%	17s	11s	11s	14s	33s
max. Drehmoment Betrieb	10 Nm 88,5 lb/in	20 Nm 177 lb/in	35 Nm 309 lb/in	55 Nm 486 lb/in	140 Nm 1239 lb/in
max. Drehmoment Start	12 Nm 106,2 lb/in	25 Nm 221 lb/in	38 Nm 359,3 lb/in	60 Nm 560 lb/in	170 Nm 1504 lb/in
Einschaltdauer (%)	75%	75%	75%	75%	75%
IP IEC 60529	IP-65	IP-65	IP-65	IP-65	IP-65
Arbeitswinkel	0° - 90°	0° - 90°	0° - 90°	0° - 90°	0° - 90°
Temperatur	-20° +70°C -4° +158°F	-20° +60°C -4° +135°F	-20° +60°C -4° +135°F	-20° +60°C -4° +135°F	-20° +60°C -4° +135°F
Schalter	4 SPDT micro	2 SPDT micro	2 SPDT micro	2 SPDT micro	2 SPDT micro
Heizung	3,55 W	4 W	4 W	4 W	4 W
Verbrauch max. Drehmoment	110 VAC/VDC 272mA 30W 220 VAC/VDC 272mA 60W	110 V 180mA (19,8w) 220 V 85mA (20,9w)	110 V 180mA (15,5w) 220 V 85mA (17,2w)	110 V 180mA (19,8w) 220 V 85mA (20,9w)	110 V 700mA (77w) 220 V 230mA (50,6w)
Anschluss	DIN 43650 ISO 4400 & C192	DIN 43650 ISO 4400 & C192	DIN 43650 ISO 4400 & C192	DIN 43650 ISO 4400 & C192	DIN 43650 ISO 4400 & C192
Gewicht	0,9 kg	1,5 kg	1,8 kg	2,0 kg	5,2 kg

